



2022

NOVATEC

QUALITY • PERFORMANCE • RELIABILITY

STIM WHEELS

HEART
PUMPING
SPEED

21



THE LATEST
HOW TO
WHAT FEEL
HAS A RIDE



FRAMING TECHNOLOGY

COMTEFA



INDEX P02

CONTENTS P04

TECHNOLOGY P06

ROAD CARBON P10

ROAD ALLOY P12

ROAD DISC P16 P18 P20 P22

OFFROAD P26 P28 P30 P36

OFFROAD XL P32 P34

HUBS P38


QUICK RELEASE/CASSETTE P40

GLOBAL P42

WHEELSET SPECS 44

CREDIT P46

VTS



TECHNO



MATRISILK

REINFORCEMENT FIBERS
EMBEDDED INTO THE CARBON
FABRIC YIELDING A MATRIX
STRUCTURE THAT INCREASES
STRENGTH & FATIGUE LIFE



HYPERTOROID

OPTIMIZED CROSS-SECTIONAL
SHAPE MEANS EXCELLENT
FRONTAL AERODYNAMICS
& MINIMIZED LATERAL
TURBULENCE



PROTEX

PROPRIETARY COATING
IMPREGNATED INTO THE
BRAKE TRACK OF OUR
CARBON RIMS FOR ENHANCED
ALL-WEATHER PERFORMANCE



TUBELESS READY

PROPRIETARY RIM PROFILE
THAT IS COMPATIBLE WITH
TUBELESS TIRE SYSTEMS
WITHOUT THE NEED FOR
LIQUID SEALANT



A.B.G.

ANTI-BITE GUARD IS A
REINFORCED STEEL RIB
INTEGRATED INTO ALLOY
CASSETTE BODY SPLINES TO
MITIGATE DAMAGE FROM
DRIVE FORCES



4 IN 1

PROPRIETARY HUB TECHNOLOGY ALLOWING CONVERSION FROM STANDARD QR, 9MM, 15MM & 20MM AXLES (FRONT) & QR, 10MM, 12MM & X12 AXLES



UNIQUE 3 IN 1

PROPRIETARY REAR HUB TECHNOLOGY ALLOWING COMPATIBILITY WITH SHIMANO, SRAM & CAMPAGNOLO CASSETTE BODIES



SEALED BEARING

TOP QUALITY JAPANESE MADE SEALED BEARINGS ENSURE THAT NOVATEC WHEELS ROLL FAST & FRICTION-FREE



REPLACEABLE BEARINGS

DOUBLE & QUAD BEARING CONFIGURATIONS ARE REPLACEABLE SHOULD THEY WEAR OUT - NOT THAT WE EXPECT THAT TO HAPPEN



HAND BUILT

ASSURANCE THAT THE WHEELSET DISPLAYING THIS MARK WAS HAND BUILT & TENSIONED BY A SKILLED & DEDICATED NOVATEC EXPERT WHEEL BUILDER



RAMBLER



R3
JETFLY
JETFLY-SL




OUR MOST VERSATILE CARBON ROAD WHEELSET IS LIGHT ENOUGH FOR CLIMBING & STIFF ENOUGH FOR CRITERIUMS. OUR SEMI-TOROIDAL 38MM DEEP RIM PROFILE IS PERFECTLY TUNED & TENSIONED WITH STAINLESS BLADED SPOKES TO LIGHTWEIGHT HUBS.

R3



- AN IDEAL, DO-EVERYTHING, 38MM DEEP, WIDE PROFILE FULL CARBON RIM
- MATRISILK STRUCTURAL MESH & PROTEX 3K ENHANCED BRAKING SURFACE
- SUPER HIGH TEMPERATURE TG RESIN PREVENTS HEAT DISTORTION
- MEDIUM DEPTH IS IDEAL BALANCE BETWEEN RIGIDITY & ON-ROAD COMPLIANCE
- HAND BUILT WITH STAINLESS AERO SPOKES & DSN NIPPLES
- ALSO AVAILABLE IN DISC CONFIGURATION WITH ASYMMETRIC RIM FOR LATERAL STRENGTH
- CLINCHER: 1,610 GRAMS/PAIR

(CLINCHER U3.0)





NOVATEC

JETFLY-SL(CLINCHER U1.0)


THE PERFECT WHEEL FOR A TRAINING RIDE, JETFLY'S 32MM-DEEP SECTION RIM FEELS LIKE RIDING ON A KNIFE-EDGE.

JETFLY




- **FULL ALLOY RIMS WITH MACHINED BRAKING SURFACE**
- **MINIMAL WEIGHT MAKES THEM CLIMB LIKE A MOUNTAIN GOAT**
- **UNIQUE 3-IN-1 REAR HUB FOR EASY COMPATIBILITY WITH**
- **SHIMANO, SRAM & CAMPY**
- **TUBELESS READY PROFILE**
- **DSN NIPPLES**
- **CLINCHER : 1,564 GRAMS/PAIR**
- **JETFLY-SL : 1,343 GRAMS/PAIR**

(CLINCHER U4.0)



JETFLY CLINCHER



JETFLY-SL CLINCHER





R24

G24

R4 DISC

R3



DISC

— — JETFLY DISC




NEW TO OUR LINE UP IS THE G24 GRAVEL WHEELSET. AT HOME ON ANY GRAVEL OR CROSS BIKE, THE G24 IS EQUIPPED WITH A CARBON RIM WITH A HEIGHT OF 28MM AND COMES IN AT A SLIM 415G KEEPING THAT ROTATIONAL WEIGHT LOW. WE ARE OFFERING HOOKLESS ON OUR G24 WITH AN INNER RIM WIDTH OF 24MM, THEY CAN TAKE A 50C TIRE NO PROBLEM AND STILL WITH TUBELESS READY, WE'RE CONFIDENT THIS WILL BECOME A FAVORITE OF THE BACK-ROAD EXPLORER.

GRAVEL



- AN IDEAL, DO-EVERYTHING, 28MM DEEP, WIDE PROFILE FULL CARBON RIM
- MEDIUM DEPTH IS IDEAL BALANCE BETWEEN RIGIDITY & ON-ROAD COMPLIANCE
- HAND BUILT WITH STAINLESS AERO SPOKES & DSN NIPPLES
- HOOKLESS/TLR
- CLINCHER: 1,575 GRAMS/PAIR

(CLINCHER U1.0)






OUR R4 DISC WHEELSET IS A NEW ADDITION TO OUR DISC CARBON WHEEL COLLECTION. AN IN-BETWEEN OUR R3S AND R5S WITH A RIM HEIGHT OF 45MM AND AN INTERNAL WIDTH UP TO 21MM WITH TUBELESS READY, THE R4 WHEELSET IS PERFECT FOR THE SERIOUS CYCLIST. WITH A RIM WEIGHT OF 470G, THE ROTATIONAL WEIGHT IS MINIMAL, AND OUR CLASSIC R SERIES SHAPE STAYS TRUE TO RACE AERO DYNAMICS. AVAILABLE WITH CENTERLOCK ONLY.

NOVATEC 45MM DISC



- AN IDEAL, DO-EVERYTHING, 45MM DEEP, WIDE PROFILE FULL CARBON RIM
- MEDIUM DEPTH IS IDEAL BALANCE BETWEEN RIGIDITY & ON-ROAD COMPLIANCE
- HAND BUILT WITH STAINLESS AERO SPOKES & DSN NIPPLES
- CLINCHER: 1,559 GRAMS/PAIR

(CLINCHER U1.0)





THE NEW UPDATED R3 DISC WHEELSET TO KEEP UP WITH THE CURRENT TRENDS. WE'VE WIDENED THE INTERNAL RIM WIDTH TO 21MM WITH TUBELESS READY GIVING YOUR TIRES A LITTLE MORE ROOM AND DECREASED THE RIM HEIGHT TO 35MM FROM 38MM KEEPS THESE IN REGULAR ROTATION THROUGHOUT YOUR BIKE STABLE SO IT'S NO PROBLEM BEING YOUR EVERYDAY WHEELSET.

NOVATEC DISC




- AN IDEAL, DO-EVERYTHING, 35MM DEEP, WIDE PROFILE FULL CARBON RIM
- MEDIUM DEPTH IS IDEAL BALANCE BETWEEN RIGIDITY & ON-ROAD COMPLIANCE
- HAND BUILT WITH STAINLESS AERO SPOKES & DSN NIPPLES
- ALSO AVAILABLE IN DISC CONFIGURATION WITH ASYMMETRIC RIM FOR LATERAL STRENGTH
- CLINCHER: 1,478 GRAMS/PAIR

(CLINCHER U3.0) ASYMMETRIC RIM



CLINCHER






THE JETFLY DISC IS OUR TRIED-AND-TRUE ALLOY ROAD DISC WHEELSET. WHETHER YOU ARE OUT FOR A LONG TRAINING RIDE OR EXPLORING NEW ROUTES, THE JETFLYS DISC CAN DO IT ALL. DUE TO THE VERSATILITY OF THIS WHEELSET, WE ARE NOW OFFERING THEM IN CENTERLOCK ONLY. THE INTERNAL WIDTH COMES WITH 20MM AND STILL OFFER IN TUBELESS READY.

MAX DISC



- **NEW WIDE PROFILE SUPERLIGHT ALLOY RIM**
- **ANTI-BITE GUARD (ABG) CASSETTE BODY**
- **RACE LEVEL FEATURES AND PERFORMANCE**
- **UNIQUE 3-IN-1 REAR HUB FOR EASY COMPATIBILITY WITH**
- **SHIMANO, SRAM & CAMPY**
- **TUBELESS READY PROFILE**
- **DSN NIPPLES**
- **CLINCHER: 1,714 GRAMS/PAIR**

(CLINCHER U4.0)





OFFROAD

M30 — FLOWTRAIL — DIA
— DIABLO



CANNONDALE

XL

DEMON XL

CRISP

M30



M30 29"




M30 29"

DSN 29



M30 27.5"


- **TRAIL POUNDING 30MM INNER WIDTH**
- **TUBELESS READY MICROPEENED RIM PROFILE**
- **HEAT CURED GRAPHICS ARE LIGHT & CAN WITHSTAND HARD OFF ROAD ABUSE**
- **AVAILABLE IN 27.5 & 29 RIM DIAMETERS**
- **DSN NIPPLES**
- **M30 27.5: 1,915 GRAMS/PAIR**
M30 29: 1,982 GRAMS/PAIR
- **AVAILABLE IN AND BOOST SPACING**



FLOWTRAIL




FLOWTRAIL 29" BOOST



FLOWTRAIL 29" BOOST


THE NAME SAYS IT ALL. FLOWTRAIL IS A PERFECT BLEND OF GRAVITY-BIASED & GO-ANYWHERE PERSONALITIES. LIGHT ENOUGH FOR CROSS COUNTRY, RESILIENT ENOUGH FOR ENDURO & PERFECT FOR EVERYDAY, FLOWTRAIL LETS YOU FIND RHYTHM ON YOUR RIDE.

FLOWTRAIL




FLOWTRAIL 27.5" BOOST

- **TUBELESS READY PROFILE - NO MORE PINCH FLATS FOR WHEN THE GOING GETS ROUGH**
- **4-IN-1 FRONT HUB EASILY CONVERTS FROM QR, 9MM, 15MM & 20MM AXLES**
- **AN ALL NEW WIDE PARABOLIC RIM CROSS SECTION RESULTS IN IMPROVED TIRE SHAPING WHILE DISSIPATING FORCES MORE EVENLY ACROSS THE RIM STRUCTURE**
- **SLEEVED RIM JOINT IS STRONGER THAN A WELDED JOINT & DOES NOT HEAT DAMAGE THE RIM**
- **A.B.G. FORTIFIED ALLOY CASSETTE BODY RESISTS DAMAGE FROM DRIVE FORCES**
- **AVAILABLE IN 27.5 & 29 RIM DIAMETERS**
- **DSN NIPPLES**
- **FLOWTRAIL 27.5 BOOST: 1,777 GRAMS/PAIR**
FLOWTRAIL 29 BOOST: 1,830 GRAMS/PAIR
- **AVAILABLE IN STANDARD AND BOOST SPACING**





DIABLO 29"



DIABLO 29"

DIABLO LIVES SILENTLY IN THE NOVATEC STABLE SOMEWHERE BETWEEN THE LOAMY TRAILS OF MISTY MOUNTAIN BLISS & THE CHAOS OF GRAVITY-FED ALPINE DESCENTS. RACKING UP PODIUM AFTER PODIUM, DIABLO IS THE WINNINGEST OFFROAD WHEELSET IN OUR LINEUP.



DIABLO 27.5"

- **TRAIL POUNDING 23MM INNER WIDTH**
- **TUBELESS READY MICROPEEDED RIM PROFILE**
- **4-IN-1 FRONT HUB FOR COMPATIBILITY WITH QR, 9MM, 15MM & 20MM FRONT AXLE SYSTEMS**
- **HEAT CURED GRAPHICS ARE LIGHT & CAN WITHSTAND HARD OFF ROAD ABUSE**
- **AVAILABLE IN 27.5 & 29 RIM DIAMETERS**
- **DSN NIPPLES**
- **DIABLO 27.5: 1,873 GRAMS/PAIR**
DIABLO 29: 1,969 GRAMS/PAIR
- **AVAILABLE IN STANDARD AND BOOST SPACING**



DIABLO



DIABLO XL 29"




DIABLO XL 29"

HARD CORE HAS NOTHING ON THE DIABLO XL. IF OUR GRAVITY WHEELS ARE BOMBPROOF THEN THE DIABLO XL IS THE BOMB - WIDER, STRONGER, T AND FASTER OVER ANY DH COURSE YOU THROW AT IT



DIABLO XL 27.5" BOOST

- **BOOST ONLY FRONT AND REAR HUB**
- **30MM INNER WIDTH**
- **ENDURO PLUS 35MM WIDTH**
- **TUBELESS READY MICROPEENED RIM PROFILE**
- **HEAT CURED GRAPHICS ARE LIGHT & CAN WITHSTAND HARD OFF ROAD ABUSE**
- **DSN NIPPLES**
- **DIABLO XL 275 BOOST: 2,048 GRAMS/PAIR**
DIABLO XL 29: 2,134 GRAMS/PAIR





DEMON XL 29" SUPER BOOST



DEMON XL 29" SUPER BOOST

THE PLACE WHERE YOU CHEERS YOUR CREW FOR EVERYTHING YOUR THANKFUL FOR, FLIP THE FUN SWITCHES AND JUST BEFORE YOU POINT YOUR RIG INTO THE VOID BELOW YOU TAKE THAT DEEP BREATH. THIS IS THE PLACE WE TREASURE THE MOST, WE LIVE FOR THOSE MOMENTS AND ALL THAT FOLLOW. THE DEMON XL IS OUR ANSWER FOR EVERYONE LOOKING FOR THE WHEELSET TO ACCOMPANY US IN THESE MOMENTS, REGARDLESS OF WHAT COMES NEXT.



DEMON XL 27.5" SUPER BOOST

- **BOOST ONLY FRONT AND REAR HUB**
- **30MM INNER WIDTH**
- **ENDURO PLUS 35MM WIDTH**
- **TUBELESS READY MICROPEENED RIM PROFILE**
- **HEAT CURED GRAPHICS ARE LIGHT & CAN WITHSTAND HARD OFF ROAD ABUSE**
- **BRASS NIPPLES**
- **DEMON XL 27.5 SUPER BOOST: 2,110 GRAMS/PAIR**
DEMON XL 29 SUPER BOOST: 2,205 GRAMS/PAIR






CRISP GREY 26"

CRISP BLACK 26"

**DESIGN AND PRODUCE A WHEELSET THAT WOULD HOLD UP TO THE ABUSE THESE GUYS THROW AT IT, LOOK RAD AND NOT BREAK THE BANK
ALL NEW SINGLE SPEED SPECIFIC HUB UTILIZING THE INTERNAL STRUCTURE OF OUR FACTOR HUBS, THIS COMBINATION ALLOWS FOR ALMOST INSTANT ENGAGEMENT
GET YOU MOVING INTO THE LINE IMMEDIATELY**

- **26MM INNER WIDTH**
- **EXTERNAL 32MM WIDTH**
- **TUBELESS READY MICROPEENED RIM PROFILE**
- **HEAT CURED GRAPHICS ARE LIGHT & CAN WITHSTAND HARD OFF ROAD ABUSE**
- **BRASS NIPPLES**
- **CRISP 26: 2,100 GRAMS/PAIR**



HUBS 2022

NOVATEC IS WELL-KNOWN FOR OUR LIGHT, SOLID SMOOTH ROLLING HUBS, FORM ROAD TO TRACK, CAMPY TO SRAM, NOVATEC AFTERMARKET HUBS SHOULD BE AT THE HEART OF EVERY WHEELSET.



SL-PRO+

- A291SB/A-SL**
- ALLOY J-HOOK HUB
- WEIGHT 60G
- SEALED BEARING 2
- SPOKE HOLES 20 24 28
- GAUGE 14
- O.L.D 100
- AXLE 9
- AXLE MATERIAL ALLOY
- P.C.D 30
- F.T.F 68.7



SP-PRO+

- AS61CB**
- CARBON STRAIGHT PULL HUB
- WEIGHT 72G
- SEALED BEARING 2
- SPOKE HOLES 20
- GAUGE 14
- O.L.D 100
- AXLE 9
- AXLE MATERIAL ALLOY
- P.C.D 31.5
- F.T.F 80.4



SP-PRO+

- D411CB-12**
- CARBON STRAIGHT PULL DISC HUB
- WEIGHT 79G
- SEALED BEARING 2
- SPOKE HOLES 24 28
- GAUGE 14
- O.L.D 100
- AXLE 12
- AXLE MATERIAL ALLOY
- P.C.D 34
- F.T.F 63.5
- AVAILABLE



SL-PRO+

- F482SB/A-SL-11S**
- ALLOY J-HOOK HUB
- WEIGHT 228G
- SEALED BEARING 4
- SPOKE HOLES 20 24 28 32
- GAUGE 14
- O.L.D 130
- AXLE 10
- AXLE MATERIAL ALLOY
- P.C.D 41 / 49
- F.T.F 56.6
- PAWLS 4



SP-PRO+

- FS62CB-11S**
- CARBON STRAIGHT PULL HUB
- WEIGHT 215G
- SEALED BEARING 4
- SPOKE HOLES 24
- GAUGE 14
- O.L.D 130
- AXLE 10
- AXLE MATERIAL ALLOY
- P.C.D 34 / 47
- F.T.F 67.8
- PAWLS 4



SP-PRO+

- D412CB-X12-11S**
- CARBON STRAIGHT PULL DISC HUB
- WEIGHT 229G
- SEALED BEARING 4
- SPOKE HOLES 24 28
- GAUGE 14
- O.L.D 142
- AXLE 12
- AXLE MATERIAL ALLOY
- P.C.D 34 / 74
- F.T.F 60.8
- PAWLS 4

SL-TEAM

D791SB-B15

- ALLOY J-HOOK DISC HUB
- WEIGHT 170G
- SEALED BEARING 2
- SPOKE HOLES 24 28 32 36
- GAUGE 14
- O.L.D 110
- AXLE 15
- AXLE MATERIAL ALLOY
- P.C.D 58/45
- F.T.F 71.2
- OFFSET 7.2
- CENTER LOCK: D791SB-CL-B15
- 15X100: D791SB-15



DIABLO



DEMON



CRISP



SL-PRO

D902SB-B12-115

ALLOY J-HOOK DISC HUB
 WEIGHT 370G
 SEALED BEARING 4
 SPOKE HOLES 32 36
 GAUGE 13 14
 O.L.D 148
 AXLE 12
 AXLE MATERIAL ALLOY - CRMO
 P.C.D 62
 F.T.F 62.1
 OFFSET 7.6
 PAWLS 4
 XD DRIVER COMPATIBLE
 MICRO SPLINE COMPATIBLE
 CENTER LOCK: D902SB-CL-B12-115

SL PRO

XD641SB-B15



ALLOY J-HOOK DISC HUB
 WEIGHT 196G
 SEALED BEARING 2
 SPOKE HOLES 32
 GAUGE 14
 O.L.D 110
 AXLE 15
 AXLE MATERIAL ALLOY
 P.C.D 58
 F.T.F 69.5
 OFFSET 5.9
 15X100:XD641SB-15

SL-PRO

DH92SB-A4A-157-MS



ALLOY J-HOOK DISC HUB
 WEIGHT 393G
 SEALED BEARING 4
 SPOKE HOLES 32
 GAUGE 14
 O.L.D 150/157
 AXLE 12
 AXLE MATERIAL ALLOY
 P.C.D 44
 F.T.F 71.4
 OFFSET 7.6
 PAWLS 4
 XD DRIVER COMPATIBLE

SL-PRO⁺

XD641SB/A-20



ALLOY J-HOOK DISC HUB
 WEIGHT 192G
 SEALED BEARING 2
 SPOKE HOLES 28 32
 GAUGE 14
 O.L.D 110
 AXLE 20
 AXLE MATERIAL ALLOY
 P.C.D 58
 F.T.F 59.5
 OFFSET 5.9

SL PRO

XD262SB-A6A



ALLOY J-HOOK DISC HUB
 WEIGHT 370G
 SEALED BEARING 4
 SPOKE HOLES 32
 GAUGE 14
 O.L.D 135/142
 AXLE 10/12
 AXLE MATERIAL ALLOY
 P.C.D 62
 F.T.F 72.9
 OFFSET 0.7
 PAWLS 6
 9T-DRIVER UNIT COMPATIBLE

QUICK RELEASE/CASSETTE

ROAD / ROAD DISC

SHIMANO/SRAM/CAMPY COMPATIBLE



VERSATILE


OUR ROAD CASSETTE BODIES ARE 8, 9, 10 & 11 SPEED COMPATIBLE. SIMPLY INCLUDE THE SPACER FOR 8, 9 & 10 SPEED GEARING & REMOVE IT FOR 11 SPEED GEARING.

MTB SHIMANO COMPATIBLE



E440

4 PAWLS WITH 40T 2 SEALED BEARINGS OD17 CASSETTE BODY



EFFICIENT

OUR ALL NEW OFF ROAD CASSETTE FEATURES A NEW 4-PAWL, OFFSET TOOTH DRIVE SYSTEM TO MINIMIZE ANY DRIVE SLACK WHICH CAN COST PRECIOUS SECONDS IN COMPETITION.

SRAM COMPATIBLE



ADAPTABLE

NOVATEC CASSETTE BODIES ARE AVAILABLE IN OPTIONS COMPATIBLE WITH 8, 9, 10 AND 11 SPEED CASSETTES FROM SHIMANO AS WELL AS THE LATEST 1X SYSTEMS FROM SRAM.

INNOVATIONS ABOUND IN NOVATEC'S LATEST FAST ENGAGEMENT CASSETTE BODY. OUR 40TOOTH RATCHET RING MATES WITH 6 PHASED PAWLS AT TWO POINTS OF ENGAGEMENT EACH FOR POSITIVE, FORWARD-DRIVING CONTACT AT EVERY 4.28 DEGREES. THIS LEVEL OF DRIVE TRANSFERS EVERY WATT OF POWER TO THE WHEELS THROUGH OUR LIGHTWEIGHT, ALLOY FREE HUB BODY WITH ABG TO TAKE THE BITE OUT OF WEAR FROM THE CASSETTE. FOUR JAPANESE SEALED CARTRIDGE BEARINGS ROLL WITH VIRTUALLY ZERO FRICTION ARE POSITIONED ALONG THE AXLE TO PERFECTLY BALANCE FORCES IMPARTED BY THE CHASSIS



SEALED BEARING

TOP QUALITY JAPANESE BEARING, ENSURING THE NOVATEC WHEELS ROLL FAST & FRICTION - FREE



REPLACEABLE BEARING

DOUBLE & QUAD BEARING CONFIGURATION ARE REPLACEABLE SHOULD THEY WEAR OUT - NOT THAT WE EXPECT THAT TO HAPPEN



4IN1

FOUR IN ONE SYSTEM, ALLOWING CONVERSION BETWEEN STANDARD QR, 9, 15 / 20 FRONT AXLES QR, 10, 12 & X12 REAR AXLES



B427

4 PAWLS WITH 27T 2 SEALED BEARINGS OD15 CASSETTE BODY



B2-427

4 PAWLS WITH 27T 2 SEALED BEARINGS OD15 LIGHT WEIGHT CASSETTE BODY



E440

4 PAWLS WITH 40T 2 SEALED BEARINGS OD17 CASSETTE BODY

**QR249 F40G R45G
QR249 TI F32G R35G**



BRAKE PADS
FULL CARBON COMPOUND
SHIMANO & CAMY FITMENTS



BEARING PULLER KIT



BEARING INSTALLER KIT



VALVE EXTENDER

42MM FOR R5
70MM FOR R9



RIM STRIPS

700C/2 9/275 SIZE
16MM & 18MM WIDTHS



26"
18MM, 21MM
& 24MM WIDTHS



TUBULESS TAPE

21MM/24MM/26MM/28MM



WHEEL AM PACKAGING



TUBULESS VALVE

35MM / 44MM



HUB & CASSETTE AM PACKAGING



SIZE	CUFT	PCS
700C	3.35	1 SET
650B	2.61	1 SET
650B+	3.43	1 SET
650B++	4.35	1 SET
26 "	2.53	1 SET
700C	12.63	3 SETS
26"	10.7	3 SETS

GLOBAL

AUSTRALIA

BICYCLE PARTS WHOLESALÉ
ADDRESS: 76-80 Micro Circuit, Dandenong, Vic 3175 Australia
TEL: +61-3-9702 9044
FAX: +61-3-9702 9144
E-MAIL:sales@bicyclepartswholesale.com.au
WEB:www.bicyclepartswholesale.com.au

AUSTRIA (EU)

MESSINGSCHLAGER GmbH & Co. KG
ADDRESS: Hassbergstrasse 45, D 96148 Baunach, Germany
TEL: +49-9544 944 445
FAX: +49-9544 944 440
E-MAIL:info@messingschlagel.com
WEB:www.novatec.messingschlagel.com

ARGENTINA

FERRARIS SRL
ADDRESS: Piedras 1321/23 (C1140ABC), Buenos Aires, Argentina
TEL/Fax: 54-11-4307-6723/6013
E-MAIL:ventas@ferrarisrl.net

BELGIUM

Dewo-Europe NV
ADDRESS: Steenstraat 16, 1570 Vollezele, Belgium
TEL: +32 - 54 56 79 81
FAX: +32 - 54 56 70 99
E-MAIL:info@dewo-europe.com
WEB:www.dewo-europe.com

CHILE

OXFORD S.A.
ADDRESS: Orden De Malta 1434, Providencia Santiago, Chile
TEL: +56-463 2000
FAX: +56-2-235 7332
E-MAIL:vheresmann@oxford.cl
WEB:www.oxford.cl

CHINA

JOY INDUSTRIAL(SHEN ZHEN) CO., LTD.
ADDRESS: Chuang Ye Road 12, The Third Industrial Zone, Shui Tian Shi Yan Town, Bao An ShenZhen, China (518108)
TEL: +86-755-2968 4800
FAX: +86-7552968 4727
E-MAIL:szsales@joy-tech.com.tw

CZECH REP. (EU)

DEMA Senica, a.s.
ADDRESS: Dlha 248, 905 01 Senica, Slovakia
TEL: +421-34-6945 240
FAX: +421-34-6945 102
E-MAIL:sport@dema.sk
WEB:www.dema.sk

GERMANY (EU)

MESSINGSCHLAGER GmbH & Co. KG
ADDRESS: Hassbergstrasse 45, D 96148 Baunach, Germany
TEL: +49-9544 944 445
FAX: +49-9544 944 440
E-MAIL:info@messingschlagel.com
WEB:www.novatec.messingschlagel.com

HUNGARY (EU)

NEUZER KFT.
ADDRESS: H-2500 Esztergom, Eotvos U.48, Hungary
TEL: +36-33-500 580
FAX: +36-33-411 116
E-MAIL:info@neuzer.hu
WEB:www.neuzer-bike.hu

INDONESIA

PT BINTANG TIMUR
ADDRESS: Jl. Anggrek Neli Murni No. 114 Slipi Jakarta Barat 11480, Indonesia
TEL: +6221-6300555
E-MAIL:sales@bintang-timur.com

ITALY

CICLI FINA srl.
ADDRESS: Via Piersanti Mattarella 2
930 10 Serradifalco (CL)
Italy
TEL: +39-0934932422
E-MAIL:ciclifinasrl@gmail.com
WEB:www.ciclifina.it

ISRAEL

MOTOFAN SAHAR 2002 LTD.
ADDRESS: Arie Regev 17 Netanya 42502, ISRAEL
TEL: +972-9-885-6602
WEB:https://moto-ofan.co.il/

JAPAN

YOSHIKAWA MFG. CO., LTD.
ADDRESS: 4-14-28 Gamo, Koshigaya, Saitama, 343-0838, Japan
TEL: +81-48-990-1735
FAX: +81-48-990-1736
E-MAIL:info@ysb-brake.co.jp
WEB:www.actionsports.co.jp

MACEDONIA

CYCLO MANIA INT.doo
ADDRESS: Radnoti Miklos 2, 21235 Temerin, Vojvodina, Serbia
TEL: +381-69-5500777
E-MAIL:office@cyclo-mania.com
WEB:www.cyclo-mania.com

MALAYSIA

HUAN SCHEN Sdn. Bhd.
ADDRESS: No.12, Jalan TIAJ 2/5, Taman Industri Alam Jaya, Bukit Cherakah, 42300 Selangor, Malaysia
TEL: +603 6038 6788
FAX: +603 6038 9788
E-MAIL:huanschen@gmail.com or info@huanschen.com.my
WEB:www.huanschen.com.my

MONTENEGRO

CYCLO MANIA INT.doo
ADDRESS: Radnoti Miklos 2, 21235 Temerin, Vojvodina, Serbia
TEL: +381-69-5500777
E-MAIL:office@cyclo-mania.com
WEB:www.cyclo-mania.com

PERU

DISARVA ASOCIADOS S.R.L.
ADDRESS: JR.Helio 5695 URB. Industrial Infantas Los Olivos JR.Luna Pizarro 120 La Victoria-Lima, Peru
TEL: +511-528 8801
FAX: +511-544 3038
E-MAIL:cesarbautista@disarva.net
WEB:www.disarva.com

PHILIPPINES

HATCH MOTO PRO CORP.
ADDRESS : #51 Guirayan St., Brgy. Dona Imelda Quezon City, Philippines
FAX: +(0632) 713-5083
CEL: +639175373612
E-MAIL:hatchmp@gmail.com

POLAND (EU)

SPEEDER
ADDRESS: Ul. Polna 5, 62-095 Murowana Goslina, Poland
TEL: +48-61 812 2051
FAX: +48-61 811 3034
E-MAIL:biuro@speeder.com.pl
WEB:www.speeder.com.pl

ROMANIA (EU)

DHS BIKE PARTS s.r.l.
ADDRESS: Str.Santuhalm 35A, 330004 Deva City, Romania
TEL: +40-372 777 999
FAX: +40-372 872 651
E-MAIL:office@dhsbikeparts.ro / comenzionline@dhsbikeparts.ro
WEB:www.dhsbikeparts.ro

RUSSIA

VELOOLIMP
ADDRESS: Elektrodnyaya Ul., D.2, Str12-14, Moscow, 111524, Russia
TEL/FAX: +7-495-788 1952
E-MAIL:veloolimp@gmail.com / shop@veloolimp.com
WEB:https://veloolimp.com/

SERBIA

CYCLO MANIA INT. doo
ADDRESS: Radnoti Miklos 2, 21235 Temerin, Vojvodina, Serbia
TEL: +381-69-5500777
E-MAIL:office@cyclo-mania.com
WEB:www.cyclo-mania.com

SLOVAKIA (EU)

DEMA Senica, a.s.
ADDRESS: Dlha 248, 905 01 Senica, Slovakia
TEL: +421-34-6945 240
FAX: +421-34-6945 102
E-MAIL:sport@dema.sk
WEB:www.dema.sk

SWEDEN

PRIME CYCLING AB
ADDRESS: Medevigatan 17, 25657 Ramloa, Sweden
TEL: +46(0) 738-200990
E-MAIL:info@prime-cycling.se
WEB:https://www.prime-cycling.se/

TAIWAN

IRON STABLE CO., LTD
ADDRESS: No.32-6, Sanfeng Rd., Houli Dist., Taichung City 421, Taiwan (R.O.C.)
TEL: 04-2557-5422
FAX: 04-2556-7528
EMAIL:contact@ironstable.com.tw

THAILAND

P.T.T. PROGRESS CO., LTD
ADDRESS: 40/577 Moo 10 Rama 2 Rd., Bangmod Jomthong Bangkok 10150 Thailand
TEL: +66 2452 0940 - 1
FAX: +66 2452 1072
MOBILE: +66 81 810 2911
E-MAIL:wcibike@yahoo.com

UKRAINE

SPORTSYSTEMS
ADDRESS: Kiev Region,Pershogo Travnja str., 49, Novi Petrivci 07354, Vyshgorod District,Ukraine
TEL: +380-44-585 7035
FAX: +380-44-585 7036
E-MAIL:vtkhoryk@sportsys.com.ua

UNITED KINGDOM & IRELAND

EXTRA (UK) LTD.
ADDRESS: PO BOX 101, Wellingborough, NN8 9HA, U.K.
TEL: +44-1933 672 170
FAX: +44-1933 672 171
E-MAIL:mailbox@extrauk.co.uk
WEB:www.extrauk.co.uk

URUGUAY

AlKeus S.A.
ADDRESS: Rondeau 1847,Uruguay
TEL: 0059829249695
E-MAIL:contaco@scott-montevideo.com.uy
WEB:http://www.scott-montevideo.com.uy

USA

BIKE FETTISH
ADDRESS: 3943 Irvine Blvd Ste 295, Irvine, CA 92563, USA
TEL: +1 (951) 817-7741
E-MAIL:sales@bikefettish.com
WEB:www.bikefettish.com

UNITED ARAB EMIRATES

FUN RIDE SPORTS
ADDRESS: 3rd Floor, Be Sport Bike Shop, Mushrif Mall, Opposite TCIF, Airport Road, Abu Dhabi, UAE
TEL: +971529426060 +971529426070
E-MAIL:info@funridesports.com or max@m@besport.ae
WEB:www.funridesports.com
SOCIAL:www.facebook.com/FunRideSports


WHEELSET SPECS 2022

MODEL Weight/pair	TYPE	RIM TYPE DEPTH	ETRTO ERD	INNER WIDTH EXTERNAL WIDTH	RIM FINISHING	WEIGHT FRONT / REAR CALCULATED	SPOKES No. J-Hook/Straight	SPOKES TYPE	SPOKES FRONT L/R (mm)	SPOKES REAR L/R (mm)	LACING FRONT/REAR	NIPPLE TYPE	EYELETS / VALVE HOLE	HUBS	HUB FINISHING	AXLE FRONT/REAR
R3 (Clin. U3.0) 1610g	Road Racing/Universa	Clincher Carbon 38mm	622-27.4 561.6MM*	20mm/27mm	UD MATRISILK PROTEX	712g 898g	20/24 Straight	Stainless Aero	L:10x273 R:10x273	L:8x270 R:16x267	F:Radial R:1X/2X	Black / 2 Red 16mm DSN Alloy	NO Ø6.5mm	XA831SB XF312SB	BLACK ANO. POLISHED	AL 9x108x11 AL 10x140x11
R3 DISC OCR-CL (Clin. U3.0) 1478g	Road Disc Brake	Clincher DISC Carbon 35mm	622-27.8 537.8MM*	21mm/28mm	UD	665g 813g	24/24 Straight	Stainless Aero	L:12x286 R:12x286	L:12x284 R:12x284	F:2X/2X R:2X/2X	Black / 2 Red 16mm DSN Alloy	NO Ø6.5mm	D411CB-CL-12 D412CB-CL-X12	UD FINISHING	AL 12x100 AL 12x142
R4 DISC -CL (Clin. U1.0) 1559g	Road Disc Brake	Clincher DISC Carbon 45mm	622-27.9 537.8MM*	21mm/28mm	UD	697g 862g	24/24 Straight	Stainless Aero	L:12x276 R:12x277	L:12x278 R:12x276	F:2X/2X R:2X/2X	Black / 2 Red 16mm DSN Alloy	NO Ø6.5mm	D411CB-CL-12 D412CB-CL-X12	UD FINISHING	AL 12x100 AL 12x142
JETFLY (U4.0) 1564g	Road Racing/ Training	Clincher Alloy 32mm	622-20 589.2MM*	20mm/25mm	BLACK MICRO PEEN	688g 876g	20/24 J-HOOK	Stainless Double Butted	L:12x277 R:12x277	L:8x268 R:16x283	F:Radial R:1X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	XA561SB XF562SB	BLACK ANO. POLISHED	AL 9x108x11 AL 10x140x11
JETFLY SL(Clin.U1.0) 1343g	Road Racing/ Training	Clincher Alloy 23.3mm	622-17 589.2MM*	17mm/21.3mm	BLACK MICRO PEEN	583g 760g	20/24 J-HOOK	Stainless Double Butted	L:10x285 R:10x285	L:8x284 R:16x291	F:Radial R:1X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	XA561SB XF562SB	BLACK ANO. POLISHED	AL 9x108x11 AL 10x140x11
JETFLY DISC-CL (U4.0) 1714g	Road Disc Brake	Clincher Alloy 32mm	622-20 572.1MM*	20mm/24mm	BLACK MICRO PEEN	786g 928g	24/28 J-HOOK	Stainless Double Butted	L:12x280 R:12x282	L:14x288 R:14x276	F:2X/2X R:3X/2X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-CL D792SB-CL-X12	BLACK ANO. POLISHED	AL 12x100 AL 12x142
G24 (U1.0) 1575g	GRAVEL	Clincher Carbon 28mm	622-24 537.8mm*	24mm/30mm	UD	724g 851g	24/24 J-HOOK	Stainless Double Butted	L:12x286 R:12x288	L:12x288 R:12x285	F:2X/2X R:2X/2X	Black 16mm DSN Alloy	NO Ø6.5mm	D791SB-CL D792SB-CL-X12	BLACK ANO. POLISHED	AL 12x100 AL 12x142
M30 27.5 (U1.0) 1915g	MTB Disc Trail	Clincher Carbon 25mm	584-30 589.2MM	30mm/37mm	UD	854g 1061g	32/32 J-HOOK	Stainless Double Butted	L:16x271 R:16x274	L:16x272 R:16x270	F:3X/3X R:3X/3X	Black 16mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
M30 29.5 (U1.0) 1982g	MTB Disc Trail	Clincher Carbon 25mm	622-30 593.8MM*	30mm/37mm	UD	881g 1101g	32/32 J-HOOK	Stainless Double Butted	L:16x290 R:16x293	L:16x291 R:16x289	F:3X/3X R:3X/3X	Black 16mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
FLOWTRAIL 27.5 (U3.1) 1777g	MTB Disc Trail	Clincher Alloy 18mm	584-23 589.2MM	23mm/27.6mm	BLACK MICRO PEEN	780g 997g	32/32 J-HOOK	Stainless Double Butted	L:16x275 R:16x279	L:16x276 R:16x274	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
FLOWTRAIL 29 (U3.1) 1830g	MTB Disc Trail	Clincher Alloy 18mm	622-23 593.8MM*	23mm/27.6mm	BLACK MICRO PEEN	796G 1034G	32/32 J-HOOK	Stainless Double Butted	L:16x294 R:16x298	L:16x295 R:16x293	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
DIABLO 27.5 BOOST (U2.1) 1873g	MTB Disc Trail	Clincher Alloy 18.5mm	584-23 589.2MM	23mm/28.5mm	BLACK MICRO PEEN	838g 1045g	32/32 J-HOOK	Stainless Double Butted	L:16x274 R:16x278	L:16x275 R:16x273	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
DIABLO 29 BOOST (U2.1) 1969g	MTB Disc Trail	Clincher Alloy 18.5mm	622-23 593.8MM*	23mm/28.5mm	BLACK MICRO PEEN	882g 1087g	32/32 J-HOOK	Stainless Double Butted	L:16x294 R:16x298	L:16x295 R:16x293	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
DIABLO XL 27.5(U2.0) 2048g	MTB DISC ENDURO	Clincher Alloy 21mm	584-30 556MM*	30mm/35mm	BLACK MICRO PEEN	914G 1134G	32/32 J-HOOK	Stainless Double Butted	L:16x272 R:16x276	L:16x272 R:16x271	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
DIABLO XL 29(U2.0) 2134g	MTB DISC ENDURO SUPER BOOST	Clincher Alloy 21mm	622-30 593.8MM*	30mm/35mm	BLACK MICRO PEEN	963G 1171G	32/32 J-HOOK	Stainless Double Butted	L:16x291 R:16x295	L:16x291 R:16x290	F:3X/3X R:3X/3X	Black / 2 Red 14mm DSN Alloy	NO Ø6.5mm	D791SB-B15 D902SB-B12	BLACK ANO. POLISHED	AL 15x110 AL 12x148
DEMON XL 27.5(U2.0)- SUPER BOOST 2110g	MTB DISC SUPER BOOST	Clincher Alloy 21mm	584-30 556MM*	30mm/35mm	BLACK MICRO PEEN	955g 1155g	32/32 J-HOOK	Stainless Double Butted	L:16x269 R:16x270	L:16x270 R:16x268	F:3X/3X R:3X/3X	SILVER 14MM BRASS NIPPLE	NO Ø6.5mm	XD641SB-B20 DH92SB-12X157	BLACK ANO. POLISHED	AL 20X110 AL 12x157
DEMON XL 29(U2.0) SUPER BOOST 2205g	MTB DISC DH BOOST	Clincher Alloy 21mm	622-30 593.8MM*	30mm/35mm	BLACK MICRO PEEN	1005g 1200g	32/32 J-HOOK	Stainless Double Butted	L:16x288 R:16x289	L:16x289 R:16x287	F:3X/3X R:3X/3X	SILVER 14MM BRASS NIPPLE	NO Ø6.5mm	XD641SB-B20 DH92SB-12X157	BLACK ANO. POLISHED	AL 20X110 AL 12x157
CRISP 2100g	DIRT JUMP	Clincher Alloy 21mm	559-26 530.5MM*	26mm/32mm	BLACK MICRO PEEN	920g 1180g	32/32 J-HOOK	Stainless Double Butted	L:16x256 R:16x258	L:16x257 R:16x257	F:3X/3X R:3X/3X	SILVER 12MM BRASS NIPPLE	NO Ø6.3mm	XD641SB XD262SB	BLACK ANO. POLISHED	AL 15X100 AL 10X135

	CONVERTIBLE TO TUBELESS	CASSETTE Shim/Stanny/Camp	MATERIAL OF CASS.BODY/COMPATIBILITY	RIM WEIGHT	BEARING SIZE	HUB WEIGHT FRONT / REAR	QUICK RELEASE	PARTS
0030	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	498g	F: #699x2 R: #6802x1 #6902x3	F: 90g R: 253g	QR261	Brake Shoers,Valve Extener,4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABC	440g	F: #6803x2 R: #15267x2 #6902x2	F: 87g R: 242g		Valve Extener,4 Spare Spoke and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	470g	F: #6803x2 R: #15267x2 #6902x2	F: 87g R: 242g		Valve Extener,4 Spare Spoke and Nipples
0030	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	518g	F: #689x2 R: #6802x1 #6902x3	F: 65g R: 235g	QR249	4 Spare Spokes and Nipples
0030	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	385g	F: #689x2 R: #6802x1 #6902x3	F: 65g R: 235g	QR249	4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	504g	F: #6902x2 R: #6902x4	F:144g R:271g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG	415g	F: #6902x2 R: #6902x4	F:144g R:271g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	470g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	490g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	415g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	440g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	440g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	490g	F: #6902x2 R: #6903x2 #17287x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	549G	F: #6804x2 R: #17287x2 #6903x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD/MS]	584G	F: #6804x2 R: #17287x2 #6903x2	F:157g R:378g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD]	549G	F: #6804x2 R: #17287x2 #6903x2	F:187g R:394g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1	Alloy ABG [XD]	584G	F: #6804x2 R: #17287x2 #6903x2	F:187g R:394g		4 Spare Spokes and Nipples
	YES	SHIM.11 UNIQUE 3in1		530G	F: #6804x2 R: #6902x4	F:185g		4 Spare Spokes and Nipples

SHIMANO
 HOLLOW
 RIMS

CREDIT



HRINKOW ADVARICS CYCLEANG TEAM P08 P10 P12 P14 P16 P18 P20 P22

KELLYS FACTORY TEAM P04 P24 P34

CTM P38

MAXIME PEYTHIEU P02 P06

CARLO GAMBIRASIO/PHOTO BY ALEX LUISE P28

SLAVIK HANNES / PHOTO BY TRÖSCH MARKUS P32 P42

DAN SHENG-SHENG CHIANG P30

MAX FREDRIKSSON P46

LUKAS KNOPF / FRONTCOVER P36

PAUL COUDERC P44





WWW.NOVATECWHEELS.COM

AMERICA EUROPE ASIA

NOVATEC WHEELS US, INC.

1164 OLD 441 N. CLAYTON,
GA. 30525
U.S.A.
CUSTOMERSERVICE@NOVATECUSA.NET
T: +1 706 408 0139

NOVATEC EU S.R.O

SADOVA 2719/3C
905 01 SENICA
SLOVAKIA
INFO@NOVATECWHEEL.EU
T: +421 948 72 96 99

NOVATEC TAIWAN (HQ)

NO. 508, SEC 4,
CHANGPING RD., DAYA DIST.,
TAICHUNG CITY, TAIWAN 42850
SERVICE@NOVATECWHEELS.COM
T: +886 4 25687150

NOVATECWHEELS SHENZHEN

NO 12 CHUANGYE ROAD
THE 3RD INDUSTRIAL ZONE
SHUITIAN VILLAGE, SHIYAN TOWN
BAOAN, SHENZHEN
CHINA 518108
SZSALES@JOY-TECH.COM.TW
T: +86 755 2968 4800